Prevalence of in Nonparametric Statistical Analysis of Medical and Other Scientific Data: Theoretical and Computational Analysis

James Boudreau[1]
Justin Ehrlich[2]
Shane Sanders[3]

September 9, 2020

I. Introduction

Simpson's Aggregation Paradox, also known as the *Yule-Simpson Aggregation Paradox*, represents an anomaly in statistics whereby two qualitatively equivalent statistical test results—each arising from one of two distinct constitutent data sets—disappears when the same statistical test is applied to the pooled data. The paradox was first put forth by Yule (1903) and later developed by Simspon (1951). While first considered strictly for the domain of parametric testing, its presence in non-parametric statistical results has recently been studied (Haunsperger, 2003; Haunsperger and Saari ,1991; Bargagliotti, 2009). Of particular importance to the present study, Haunsperger and Saari (1991) find conditions for *Simpson reversals* in rank sum statistical testing, where the term *Simpson reversal* is used synonymously with the term *instances of Simpson's Aggregation Paradox* herein. In general, the paradox has been found to affect statistical results in many important scientific domains, including environmental and related ecological research (see, e.g., Pineiro et al., 2006 or Allison and Goldberg, 2002

occur if the sign test for matched pairs is applied to the primitive and pooled data sets. They also show evidence of *Simpson reversals* for the *WMW Test*.

Despite the important theoretical contributions by Haunsperger and Saari (1991) and Nagaraja and Sanders (2020), there

(|) − (|) > for this range of score margins in the *2x5* case, and a *reversal* cannot occur.

While the overall likelihood of *reversal* is relatively low for small sample cases of rank sum scoring (e.g., relative to a standard -value)

generates the closest margin of victory in each case (i.e., 1 rank sum unit for *n*-odd cases and 2 rank sum units for *n*-even cases). While the *overall* likelihood of *reversal* is consistently below 0.02 for computed cases, *reversals* are found to be much more prevalent for certain initial sequences. In the 2 7 case, the maximum initial sequence conditional likelihood of *reversal* is approximately 0.22, for example. The results of Figure 3 suggest that it is important to consider not only the statistical test but also the particular data (sequence) of interest when assessing prevalence of *Simpson reversals*. As with the overall likelihood of *reversal* for computed cases, we find that the maximum likelihood of *reversal* at the initial sequence level of the data strictly increases from the to + 2 case for the range of computed cases.

V. Conclusion

In this paper we have begun an investigation into the likelihood of *Simpson reversals*. Here our sole theoretical result was a sufficiency condition, but in a future paper we plan to provide both sufficient and necessary conditions in order to provide more accurate bounds on the score differential between groups and that either guarantee the existence of a *reversal* or make one impossible. Such results will then allow us to streamline our computational methods even more in order to assess larger sized groups.

The importance of being able to handle large samples is something our preliminary results here indicate. Though this is a first approach, we have shown that group size has an impact on the likelihood of *reversals*: as increases, *reversals* become more possible in general. The individual cases of sequences displaying higher likelihoods of *reversal* themselves also see higher heights as increases. More generally, of course, empirical data samples usually have relatively large . This paper is a first step toward analyzing such data, and our future papers will continue to build on it.

References

Allison, V. J., & Goldberg, D. E. (2002). Species-Level versus Community-Level Patterns of Mycorrhizal Dependence on Phosphorus: An Example of Simpson's Paradox. (3), 346-352.

Bargagliotti, A. E. (2009). A i0

Foster, G., & Rahmstorf, S. (2011). Global temperature evolution 1979-2010. (4), 1-8.

Haunsperger, D. B. (2003). Aggregated statistical rankings are arbitrary. (2), 261-272.

Haunsperger, D. B., & Saari, D. G. (1996). Paradoxes in nonparametric tests. (1), 95-104.

Kock, N. (2015). How likely is Simpson's Paradox in path models? (1), 1-7.

Nagaraja, H., & Sanders, S. (2020). The aggregation paradox for statistical rankings and nonparametric tests. (3), e0228627.

Pavlides, M. G., & Perlman, M. D. (2009). How likely is Simpson's paradox? (3), 226-233.

Pineiro, G., Oesterheld, M., Batista, W. B., & Paruelo, J. M. (2006). Opposite changes of whole-soil vs. pools C:N ratios: a case of Simpson's paradox with implications on nitrogen cycling. , 804-809.

Simpson, E. H. (1951). The interpretation of interaction in contingency tables. , 238-241.

Yule, G. U. (1903). Notes on the theory of association of attributes in statistics. (2), 121-134.

Appendix I: Computational Code

```
import java.io.BufferedWriter;
import java.io.FileWriter;
import java.io.IOException;
import java.util.Arrays;
import java.util.HashMap;
import java.util.Map;
import java.util.Scanner;
import java.util.SortedSet;
import java.util.TreeSet;
import java.util.logging.Level;
import java.util.logging.Logger;

/**
 *
 * @author Justin Ehrlich
 */
```

```
public class SimpsonsParadox {

    private static int numGroups = 0;
    private static int numDataPoints = 0;

    int numPossibleInd = 0;
    int numIndWeakOnlyAnomalyTypeI = 0;
    int numIndWeakOnlyAnomalyTypeII = 0;
    int numPossibleCycles = 0;
    int numAnomaly = 0;
    int firstDegreeTransativityViolations = 0;
    int numWeakAnomaly = 0;
    int secondDegreeTransativityViolations = 0;
    int thirdDegreeTransativityViolations = 0;


    long numWinnerChanged = 0;
    long numWinnerChangedPossible = 0;

    long topNumWinnerChanged = 0;
    long topNumWinnerChangedPossible = 0;
    String topInitialSequence = "";

    Map<Long, Long> numIndependenceViolationCategoryOccurences = new HashMap<Long
, Long>();
    Map<Long, Long> numIndependenceViolationCategoryCycles = new HashMap<Long, Lo
ng>();


    Map<Long, Long> numSimponsParadoxViolationHighScore = new HashMap<Long, Long>
();
    Map<Long, Long> numSimponsParadoxViolationPossibleHighScore = new HashMap<Lon
g, Long>();

    public SimpsonsParadox() {
    }



    private void createShuffledEvent(String dataPoints, String originalDataPoints
, int numGroups, int
```

```
            numWinnerChangedPossible++;
            if(winner == ' ' || originalWinner == ' '){ //weak
                return;
            }
            if(winner != originalWinner){
                numWinnerChanged++;
            }
            return;
        }
        if(currentBin >= numBins){
            //only allow for the correct number of bins. starts at 0 so should no
t equal numBins
            return;
        }
        for(int subsetSize=0; subsetSize <= originalDataPoints.length()-
dataPointsAdded; subsetSize++){
            String preString = dataPoints.substring(0, dataPointsAdded+currentBin
); //endIndex is exclusive, startIndex is inclusive
            String postString = dataPoints.substring(dataPointsAdded+currentBin);
            createShuffledEvent(preString + originalDataPoints.substring(dataPoin
tsAdded, dataPointsAdded+subsetSize) +
                postString,originalDataPoints,numGroups, numBins, currentBin+1, d
ataPointsAdded+subsetSize, originalWinner);

        }
    }
    //return ' ' if winner is tied
    private char findDependentWinner(String dataPoints, int numTeam){
        char[] groups = new char[numTeam];
        for(int i=0; i<numTeam; i++){
            groups[i] = (char) ('a' + (char)i);
        }
        int[] groupsScores = new int[numTeam];


        int counter = 0;
        for (int i = 0; i < dataPoints.length(); i++) {
            counter++;
            for(int j=0; j<numTeam; j++){
                if(dataPoints.charAt(i) == groups[j]){
```

'a'

```
    int minIndex = 0;
    for (int i = 0; i < numTeam; i++){
        if(groupsScores[i] < min){
            min=groupsScores[i];
            minIndex = i;
        }
    }
    //detect tie
    for(int i = 0; i < numGroups; i++){
        if(i != minIndex){
            if(groupsScores[i] == groupsScores[minIndex]){
                return(' ');
            }
        }

    }
    return(groups[minIndex]);
}


private int findDependentWinnerScore(String dataPoints, int numTeam){
    char[] groups = new char[numTeam];
    for(int i=0; i<numTeam; i++){
        groups[i] = (char) ('a' + (char)i);
    }
    int[] groupsScores = new int[numTeam];


    int xScore = 0;
    int yScore = 0;
    int counter = 0;
    for (int i = 0; i < dataPoints.length(); i++) {
        counter++;
        for(int j=0; j<numTeam; j++){
            if(dataPoints.charAt(i) == groups[j]){
                groupsScores[j] = groupsScores[j]+counter;
            }
        }
    }
    int min=groupsScores[0];
    int minIndex = 0;
    for (int i = 0; i < numTeam; i++){
        if(groupsScores[i] < min){
            min=groupsScores[i];
            minIndex = i;
```